

## LED Refrigerated Case Light

### Features

- \* 120V ~ 277V input. 24V constant voltage power supply
- \* Clear PC Lens - Vapor tight / Moisture proof
- \* Adjustable light direction - Offers even light
- \* Easy replace existing freezer light
- \* Min starting temperature: -30C
- \* PF > 0.95, THD < 20
- \* ETL listed
- \* DLC listed



### Left & Right Door Light System

Model	Input	Output Wattage	CCT	CRI	Lumen (nom)	Dimensions (L x W x H)	Finish	PF
60-18W-4000K	DC 24V	18W	4000K	> 80	1620	57.0" x 1.2" x 1.1"	Aluminum / PC	> 0.95
72-18W-4000K	DC 24V	18W	4000K	> 80	1620	69.0" x 1.2" x 1.1"	Aluminum / PC	> 0.95
60-18W-5000K	DC 24V	18W	5000K	> 80	1800	57.0" x 1.2" x 1.1"	Aluminum / PC	> 0.95
72-18W-5000K	DC 24V	18W	5000K	> 80	1800	69.0" x 1.2" x 1.1"	Aluminum / PC	> 0.95

### Center Light System

Model	Input	Output Wattage	CCT	CRI	Lumen (nom)	Dimensions (L x W x H)	Finish	PF
60-18W-4000K	DC 24V	18W	4000K	> 80	3240	57.0" x 1.2" x 1.1"	Aluminum / PC	> 0.95
72-18W-4000K	DC 24V	18W	4000K	> 80	3240	69.0" x 1.2" x 1.1"	Aluminum / PC	> 0.95
60-36W-5000K	DC 24V	36W	5000K	> 80	3560	57.0" x 2.2" x 1.1"	Aluminum / PC	> 0.95
72-36W-5000K	DC 24V	36W	5000K	> 80	3560	69.0" x 2.2" x 1.1"	Aluminum / PC	> 0.95

\* Constant Voltage Power Supply - Samsung 120V ~ 277V input, 24V DC output, 96W