

Ultra Thin LED Panel Light

Features

- Ultra thin LED panel light
- Replace 2' x 2' troffer
- 0-10v dimming standard
- High lumen efficiency (>110lm/W)
- Rated 100,000 hours LED chip life
- DLC Premium Listed
- ETL/cETL Listed
- 5 years limited warranty



Dimensions (mm)

	Dimensions
TRD-TR-2x2-50W-DIM 4000K	23.7" x 23.7"
TRD-TR-2x2-50W-DIM 5000K	23.7" x 23.7"



Specifications

Model	Input	Wattage	CCT	CRI	Lumen*	Type	Dimmable	PF
TRD-TR-2x2-40W-DIM 4000K	120-277V	40W	4000K	> 80	4600	2'x2' panel	Yes	> 0.90
TRD-TR-2x2-40W-DIM 5000K	120-277V	40W	5000K	> 80	4670	2'x2' panel	Yes	> 0.90

*nominal lumen output

Features

- Ultra thin LED panel light
- Replace 2' x 4' troffer
- 0-10v dimming standard
- High lumen efficiency (>110lm/W)
- Rated 100,000 hours LED chip life
- DLC Premium Listed
- ETL/cETL Listed
- 5 years limited warranty



Dimensions (mm)

	Dimensions
TRD-TR-2x4-50W-DIM 4000K	47.7" x 23.7"
TRD-TR-2x4-50W-DIM 5000K	47.7" x 23.7"



Specifications

Order Code	Input	Wattage	CCT	CRI	Lumen*	Type	Dimmable	PF
TRD-TR-2x4-50W-DIM 4000K	120-277V	50W	4000K	> 80	5990	2'x4' panel	Yes	> 0.90
TRD-TR-2x4-50W-DIM 5000K	120-277V	50W	5000K	> 80	6130	2'x4' panel	Yes	> 0.90

*nominal lumen output