## **COMMERCIAL LIGHTING DEVICES**

# Elements



TCP's LED Security Light combines the look of a traditional barn light with the benefits of LED. An efficient alternative to HID, these security lights deliver bright uniform light while providing energy savings. A long 50,000 hour rated life significantly decreases maintenance labor and material costs over the life of the fixture.

The robust die-cast aluminum housing incorporates an impact resistant acrylic lens. An integrated button photocell is standard for dusk-to-dawn control. The security light mounts directly to a wall or horizontal arm up to 1 5/8" O.D. for easy installation or retrofit of traditional luminaires.

- Site Lighting
- Security Lighting
- Entrances
- Perimeters









## **Applications**

This product family can be effectively used in outdoor wall mount or horizontal arm mount locations. Commercial, industrial, and rural exterior lighting; parking lot, cargo door, high wall, area and security.

#### Construction

- Die-cast aluminum housing
- Impact resistant acrylic lens
- Durable silver powdercoat
- Mounts to a wall or horizontal arm up to 1 5/8" O.D
- Operating Temperature: -40°C to 45°C.

#### **Electrical**

- cULus wet location rated
- Easily access wiring for quick installation
- System rated for long 50,000 hour life
- Efficiently delivers up to 140 LPW

### **Optics**

• Prismatic acrylic lens









To view our DLC qualified products, please consult the DLC Qualified Products List at www.designlights.org/qpl.




#### Listings

cULus Listed – wet location rated RoHS Compliant DLC v4.4 Standard

#### Warranty


Five year limited warranty against defects in manufacturing

## Dimensions



Weight

27W: 2.205lb 40W: 2.403lb



10.82" (275mm)

| LED Security Light Available Part Numbers |  |        |         |     |           |              |       |     |               |           |           |           |
|---|--|--------|---------|-----|-----------|--------------|-------|-----|---------------|-----------|-----------|-----------|
| Item #                                    | Description                              | LUMENS | WATTAGE | LPW | VOLTAGE   | POWER FACTOR | ССТ   | CRI | LIFE<br>(HRS) | L<br>(IN) | H<br>(IN) | W<br>(IN) |
| RSLUA 1 40KPCSV                           | LED Security Light Non Dim Button PC 40K | 3,800  | 27      | 141 | 120 - 277 | > 0.9        | 4000K | >70 | 50,000        | 10.82     | 4.33      | 8.07      |
| RSLUA 1 50KPCSV                           | LED Security Light Non Dim Button PC 50K | 3,900  | 27      | 144 | 120 - 277 | > 0.9        | 5000K | >70 | 50,000        | 10.82     | 4.33      | 8.07      |
| RSLUA240KPCSV                             | LED Security Light Non Dim Button PC 40K | 5,500  | 40      | 138 | 120 - 277 | > 0.9        | 4000K | >70 | 50,000        | 10.82     | 4.33      | 8.07      |
| RSLUA250KPCSV                             | LED Security Light Non Dim Button PC 50K | 5,700  | 40      | 143 | 120 - 277 | > 0.9        | 5000K | >70 | 50,000        | 10.82     | 4.33      | 8.07      |

COMMERCIAL LIGHTING DEVICES 188 South Service Rd Stoney Creek, Ontario L8E 3H6 905 662 9526 cld@cldinc.ca www.cldinc.ca