

HTY I

## **E-SERIES**

**ELECTRONIC DRIVERS** Constant Voltage

An electronic Class 2, phase dimmable LED driver with an extremely compact, low profile aluminum case making it the perfect choice for under cabinet lighting, kick/cove lighting, mirror lighting and multiple other residential and commercial lighting fixture applications.

## **ELECTRONIC** SINGLE CHANNEL

Constant Voltage Phase Dimmable 120VAC Input

12 OR 24VDC Output LISTED OR RECOGNIZED Enclosure



## 120VAC Input | SINGLE Channel 12 OR 24VDC Output | LISTED Enclosure with Junction Box

Part Number	Max Load	Input	Output	Dimming	Class 2	Environment
E20L12DC	20W	120VAC	12VDC	Phase	Yes	Dry/Damp/NEMA 3R
E40L12DC	40W	120VAC	12VDC	Phase	Yes	Dry/Damp/NEMA 3R
E60L12DC	60W	120VAC	12VDC	Phase	Yes	Dry/Damp/NEMA 3R
E20L24DC	20W	120VAC	24VDC	Phase	Yes	Dry/Damp/NEMA 3R
E40L24DC	40W	120VAC	24VDC	Phase	Yes	Dry/Damp/NEMA 3R
E60L24DC	60W	120VAC	24VDC	Phase	Yes	Dry/Damp/NEMA 3R
E75L24DC	75W	120VAC	24VDC	Phase	Yes	Dry/Damp/NEMA 3R
E96L24DC	96W	120VAC	24VDC	Phase	Yes	Dry/Damp/NEMA 3R

120VAC Input   SINGLE Channel 12 OR 24VDC Output   RECOGNIZED Enclosure with Junction Box									
Part Number	Max Load	Input	Output	Dimming	Class 2	Environment			
E20R12DC	20W	120VAC	12VDC	Phase	Yes	Dry/Damp/Wet/IP67			
E40R12DC	40W	120VAC	12VDC	Phase	Yes	Dry/Damp/Wet/IP67			
E60R12DC	60W	120VAC	12VDC	Phase	Yes	Dry/Damp/Wet/IP67			
E20R24DC	20W	120VAC	24VDC	Phase	Yes	Dry/Damp/Wet/IP67			
E40R24DC	40W	120VAC	24VDC	Phase	Yes	Dry/Damp/Wet/IP67			
E60R24DC	60W	120VAC	24VDC	Phase	Yes	Dry/Damp/Wet/IP67			
E75R24DC	75W	120VAC	24VDC	Phase	Yes	Dry/Damp/Wet/IP67			
E96R24DC	96W	120VAC	24VDC	Phase	Yes	Dry/Damp/Wet/IP67			



## **Key Features**

- Super Compact Aluminum Case
- Wiring Compartments with Knock-Outs for Clean and Easy Installation
- Auto-Reset Protection for Short Circuits & Over-Voltage
- Flicker-Free Dimming to 1% with any Standard MLV TRIAC Dimmer
- NEMA 3R Rated Enclosure for Indoor and Outdoor Use
- UL 8750, Class 2
- Component Signage Listing Certification: UL 879 CSA 22.2 No. 207-M89 (recognized version only)



**E-SERIES LISTED** 6.77" L x 2.67" W x 1.30"H 2 = 1 / 3 BR

